

HTTP Based Sender Id API

Issue 1.3
June 2015

HTTP ACCESS MODEL

INTRODUCTION

The platform exposes a HTTP interface to submit Sender id to its SMS Gateway for Approval.

To submit request using the HTTP interface, a client has to use GET Method.

TERMINOLOGY

param_name denotes a parameter in a HTTP request

GLOSSARY

URL	Uniform Resource Locator
HTTP	Hyper Text Transfer Protocol
API	Application Program Interface

PARAMETERS

<i>usr</i> (Mandatory)	User Name	
<i>pwd</i> (Mandatory)	Password	
<i>sender</i> (Mandatory)	The source / sender address	
<i>purpose</i> (Mandatory)	Purpose of the Sender Id	
<i>Message</i> (Mandatory)	Sample of Message	

EXAMPLE

[http://192.111.149.178/sender_api.php?usr=xxxxxx&pwd=xxxxxx&sender=xxxxxx&purpose=xxxxxxxxxx&message=Sample_Message\(URL Encoded\)](http://192.111.149.178/sender_api.php?usr=xxxxxx&pwd=xxxxxx&sender=xxxxxx&purpose=xxxxxxxxxx&message=Sample_Message(URL%20Encoded))

ERROR Description:

Error Number	Description
-900	Sender Not Allowed on Promotional Account
-800	Sender Id is Blacklisted
-700	Sender Id Already Approved
-600	Sender Id Pending for Approval
-500	Error in Submitting. Pls Contact Support
-400	Allotted Number of Sender id Exhausted. Pls Contact Support
-300	Sender id Can be only 6 Characters Alphabetic
-200	Authentication Failure
-100	Invalid Syntax or No data! send vars usr, pwd, sender id, purpose